SUB12



Subwoofer

Product Sheet \rightarrow English



SUB12


The Sub12 is a powerful subwoofer designed to extend the low frequency capabilities of any near or midfield monitoring system down to 22 Hz.

Optimized for accurate bass output

A sturdy special woofer with extended cone travel and a heavy-duty coil have been optimized for accurate reproduction from a bass reflex enclosure. The downfiring bass reflex tube avoids intrusive ventilation noise because of its generous size and shape. The PWM amplifier produces over 90% efficiency and can handle critical passages without overheating for long periods of time. An additional output allows you to cascade as many subwoofers as needed.

The Sub12 subwoofer provides a precise combination of low cutoff frequency (-3 dB at 22 Hz) and an undistorted high sound pressure level [115 dB SPL at 1 m].

Basic technical data





- → 22 Hz 150 Hz
- → Max. peak SPL at 1 m: >115 dB
- → 5 Year Warranty



Moreover, the Sub12 sounds extremely tight, without the distraction of a lesser subwoofer's harmonic distortion and resonances, which when heard, will immediately clue your ears to the location of the subwoofer.

5 YEAR

WARRANTY

[Andy Hong / TAPEOP]

For 3 years I tried other models in the same price range, or slightly more expensive. This is the one I liked. I enjoy being able to dispense the volume and ability to select frequency cutoff (some sub, 85 Hz is only available on the ADAM you can choose).

[Audiofanzine]



BERLIN, GERMANY

T +49 30-863 00 97-0 F +49 30-863 00 97-7 ADAM AUDIO UK

EMAIL: UK-INFO@ADAM-AUDIO.COM

ADAM AUDIO USA INC.

EMAIL: USA-INFO@ADAM-AUDIO.COM

